
RAPIDO C Rough-in for triple volume control 27 625 MODEL # 35032

Pure Freude an Wasser



GROHE America, Inc | 200 North Gary Avenue, Suite G, Roselle, IL 60172 Phone: +1 (800) 444-7643 | Fax: +1 (800) 225-2778 | us-customerservice@grohe.com





Pressure (psi) Pressure loss curve without downstream resistance one valve opened two valves opened 60 three valves opened 45 30 60 90 148 17.1 19.1 20.9 85 12.1 17.1 41.8 24.1 29.6 34.1 38.2 12.5 25 37.5 50 62.5 75 ____ 21.7 30.7 37.6 43.4 48.6 53.2 Q (gal/min) g al/min

ADA

Product Description: Rough-in for triple volume control 27 625

Standard Specification:

- \bullet For grid installation of Grohtherm Custom Shower system and GrohFlex ${}^{\rm M}$
- Built-in box with removable protection cover
- For masonry and drywall installation
- Fixing points for front and back wall
- Body of DR brass
- 3 inlets and 3 outlets
- Pre-assembled ceramic headpart 3/4"
- Connection thread 1/2" NPT
- 3/4" ceramic cartridge (90° turn)

Applicable Codes & Standards:

- Energy Policy Act of 1992
- ASME A112.18.1/CSA B125.1
- ICC/ANSI A117.1

Color: (35032 000 no colour